

30W

LONG LIFE CHROMOGENIC INTENSITY DISSIPATE HEAT LOW ENERGY CONSUMPTION LOW LIGHT ATTENUATION

PRODUCT FEATURES

- High strength of shell structure.
- High heat dissipation speed keeps the chip cool at all times, maximizes the illumination of the chip, and greatly delays the life of the chip.
- Ultra clear lens, clear and natural imaging, 50% longer imaging length and 1 time larger imaging area.
- The projection direction of lamps can be adjusted at will.
- Adopt OSRAM chip lamp beads.
- The lamp is directly waterproof lp67.

MODEL	WT-GP11030		
PROJECTION DISTANCE	1m-10m (dark environment)		
LIGHT SOURCE TYPE	Osram chip		
LIGHT SOURCE POWER	30W LED		
LIGHT SOURCE LIFE	50000H		
LUMINOUS FLUX	3600LM		
COLOR TEMPERATURE	7000K		
LAMP SPECIFICATION	F0,3 lens		
BEAM ANGLE	10~20 degrees		
POWER SUPPLY TYPE	Customized power supply		
VOLTAGE	DC 10-80V/be used for forklift		
OVERALL POWER	30W		
DEGREE OF PROTECTION	IP67		
PRODUCT WEIGHT	1kg		
PACKAGE SIZE	175X130X100mm		
Unit price is included 1-2 colors lens / Stirless logo			





30W / 50W

LONG LIFE CHROMOGENIC INTENSITY DISSIPATE HEAT LOW ENERGY CONSUMPTION LOW LIGHT ATTENUATION




PRODUCT FEATURES

- All aluminum alloy metal shell, high structural strength, paint baking or sand oxidation treatment.
- Cold air technology can keep the chip cool at all times, maximize the illumination of the chip, and greatly delay the life of the chip.
- Four piece ultra clear lens, with clear and natural imaging, 50% longer imaging length and 1 time larger imaging area.
- The pattern can be rotated or stationary, controlled by switches, and the projection direction of lamps can be adjusted at will.
- It can project a pattern, the projection content can be customized, and the pattern can be changed manually.
- Adopt OSRAM chip lamp beads.
- The lamp is directly waterproof Ip65.

APPLICABLE PLACES

•		
MODEL	WT-D19030	WT-D19050
PROJECTION DISTANCE	1m-6m (dark environment)	1m-10m (dark environment)
LIGHT SOURCE TYPE	Osram chip	Osram chip
LIGHT SOURCE POWER	35W LED	50W LED
LIGHT SOURCE LIFE	50000H	50000H
LUMINOUS FLUX	3200LM	4800LM
COLOR TEMPERATURE	7000K	7000K
LAMP SPECIFICATION	38/22mm	38/22mm
BEAM ANGLE	20 degrees	20 degrees
SHELL MATER I AL	High quality aluminum alloy	High quality aluminum alloy
POWER SUPPLY TYPE	Customized power supply	Customized power supply
RATED VOLTAGE	AC85V-260V	AC85V-260V
OVERALL POWER	30W	50W
DEGREE OF PROTECTION	IP65	IP65
PRODUCT WEIGHT	2,3KG	2,3KG
PACKAGE SIZE	250X190X230mm	350X190X230mm





80W

LONG LIFE CHROMOGENIC INTENSITY DISSIPATE HEAT LOW ENERGY CONSUMPTION LOW LIGHT ATTENUATION





PRODUCT FEATURES

- All aluminum alloy metal shell, high structural strength, paint baking or sand oxidation treatment,
- Cold air technology can keep the chip cool at all times, maximize the illumination of the chip, and greatly delay the life of the chip.
- Four piece ultra clear lens, with clear and natural imaging, 50% longer imaging length and 1 time larger imaging area.
- The pattern can be rotated or stationary, controlled by switches, and the projection direction of lamps can be adjusted at will.
- It can project a pattern, the projection content can be customized, and the pattern can be changed manually.
- · Adopt OSRAM chip lamp beads.
- The lamp is directly waterproof Ip65.

APPLICABLE PLACES

MODEL	WT-D19080	
PROJECTION DISTANCE	3m-15m (dark environment)	
LIGHT SOURCE TYPE	Osram chip	
LIGHT SOURCE POWER	80W LED	
LIGHT SOURCE LIFE	50000H	
LUMINOUS FLUX	8500LM	
COLOR TEMPERATURE	8000K	
LAMP SPECIFICATION	38/22mm	
BEAM ANGLE	10~20 degrees	
SHELL MATERIAL	High quality aluminum alloy	
POWER SUPPLY TYPE	Customized power supply	
RATED VOLTAGE	AC85V-260V	
OVERALL POWER	80W	
DEGREE OF PROTECTION	IP65	
PRODUCT WEIGHT	6,0KG	
PACKAGE SIZE	430X210X270mm	





100W / 150W / 200W

LONG LIFE CHROMOGENIC INTENSITY DISSIPATE HEAT LOW ENERGY CONSUMPTION LOW LIGHT ATTENUATION




PRODUCT FEATURES

- All aluminum alloy metal shell, high structural strength, paint baking or sand oxidation treatment.
- Cold air technology can keep the chip cool at all times, maximize the illumination of the chip, and greatly delay the life of the chip.
- Four piece ultra clear lens, with clear and natural imaging, 50% longer imaging length and 1 time larger imaging area.
- The pattern can be rotated or stationary, controlled by switches, and the projection direction of lamps can be adjusted at will.
- It can project a pattern, the projection content can be customized, and the pattern can be changed manually.
- · Adopt OSRAM chip lamp beads, Meanwell power supply.
- The lamp is directly waterproof lp65.

APPLICABLE PLACES

MODEL	WT-D19100	WT-D19150	WT-D19200
PROJECTION DISTANCE	3m-20m (dark environment)	3m-25m (dark environment)	4m-30m (dark environment)
LIGHT SOURCE TYPE	Osram chip	Osram chip	Osram chip
LIGHT SOURCE POWER	100W LED	150W LED	200W LED
LIGHT SOURCE LIFE	50000H	50000H	50000H
LUMINOUS FLUX	8500LM	12000LM	15000LM
COLOR TEMPERATURE	8000K	8000K	8000K
LAMP SPECIFICATION	38/22mm	38/22mm	38/30mm
BEAM ANGLE	10~20 degrees	10~20 degrees	10~20 degrees
SHELL MATER I AL	High quality aluminum alloy	High quality aluminum alloy	High quality aluminum alloy
POWER SUPPLY TYPE	Meanwell power supply	Meanwell power supply	Meanwell power supply
RATED VOLTAGE	AC85V-260V	AC85V-260V	AC85V-260V
OVERALL POWER	100W	150W	200W
DEGREE OF PROTECTION	IP65	IP65	IP65
PRODUCT WEIGHT	6.0KG	6.0KG	8.0KG
PACKAGE SIZE	430X210X270mm	430X210X270mm	430X210X270mm





300W / 400W / 600W

LONG LIFE CHROMOGENIC INTENSITY DISSIPATE HEAT LOW ENERGY CONSUMPTION LOW LIGHT ATTENUATION



PRODUCT FEATURES

- All aluminum alloy metal shell, high structural strength, paint baking or sand oxidation treatment.
- Cold air technology can keep the chip cool at all times, maximize the illumination of the chip, and greatly delay the life of the chip.
- Four/Six piece ultra clear lens, with clear and natural imaging, 50% longer imaging length and 1 time larger imaging area.
- The pattern can be rotated or stationary, controlled by switches, and the projection direction of lamps can be adjusted at will.
- It can project a pattern, the projection content can be customized, and the pattern can be changed manually.
- Adopt OSRAM chip lamp beads, Meanwell power supply.
- The lamp is directly waterproof lp65.

APPLICABLE PLACES

MODEL	WT-D19300	WT-D19400	WT-D19600
PROJECTION DISTANCE	6m-50m (dark environment)	10m-100m (dark environment)	10m-150m (dark environment)
LIGHT SOURCE TYPE	Osram chip	Osram chip	Osram chip
LIGHT SOURCE POWER	300W LED	400W LED	600W LED
LIGHT SOURCE LIFE	50000H	50000H	50000H
LUMINOUS FLUX	24000LM	36000LM	42000LM
COLOR TEMPERATURE	8000K	8000K	8000K
LAMP SPECIFICATION	38/30mm	53/45mm	55/40mm
BEAM ANGLE	10~20 degrees	10~20 degrees	10~50 degrees
SHELL MATER I AL	High quality aluminum alloy	High quality aluminum alloy	High quality aluminum alloy
POWER SUPPLY TYPE	Meanwell power supply	Meanwell power supply	Meanwell power supply
RATED VOLTAGE	AC85V-260V	AC85V-260V	220V-50HZ
OVERALL POWER	300W	400W	600W
DEGREE OF PROTECTION	IP65	IP65	IP65
PRODUCT WEIGHT	10KG	10KG	10KG
PACKAGE SIZE	520X350X220mm	670X390X520mm	550X230X320mm



